

TeamPoS 2000 Lite

*The Point-of-Sale
Terminal for
value conscious
retailers*



The compact, adaptable, and entry-level in-store system that will meet all your retailing needs.

Easily managed and simple to maintain, TeamPoS 2000 Lite is a PoS terminal that drives down your total cost of ownership.



Open Platform

TeamPoS 2000 Lite is fully compliant with Windows®98, Windows®2000, and Microsoft® DOS operating systems.

Performance

TeamPoS 2000 Lite comprises an industry-standard PC board, Intel®Celeron 566Mhz processor and a

choice of options including CD ROM, displays, printers and other PoS peripherals allowing retailers to select the performance and functionality required for their specific retail environment.

Rugged, Reliable Performance

TeamPoS 2000 Lite can withstand the rigours of the harshest retail environments, such as typical temperature, humidity, dust and dirt, vibrations and electrostatic discharge etc.

TeamPoS Heritage

TeamPoS 2000 Lite retains some of the market-leading features and benefits from the TeamPoS 2000, including:

- Ergonomics - Can be installed and used in a stacked or dispersed configuration, with cable management and optimum lengths available
- Mains Power - All of the peripherals can be driven from one AC input which means no AC adapters or excess power cables
- Expansion - TeamPoS 2000 Lite provides easy component expansion and migration as your business and application requires it
- Long Lifecycle - TeamPoS 2000 Lite is a long term product with typically a 3-4 year lifecycle and 5 years support there after

Maintenance Made Easy

Designed for easy insertion and removal of major components and expansion cards.

Front panel

The front panel can be removed while the display, printer and other POS peripherals remain mounted on top of the control unit, for easy insertion and removal of the hard disk.

Service Accessibility

The controller has easily-removable side and top access panels for 'No-tools required' access to major components for replacement or upgrade.



CD-ROM drive (Option)

A CD-ROM drive can be installed, allowing easy and convenient software installation.

Peripheral Connections

Designed for easy connection and swap-out of retail peripherals allowing you to consider using store staff for front-line swap outs to help reduce your maintenance charges and downtime.



The TeamPoS 2000 Lite provides all of the peripheral and power connectivity from its NLX-format motherboard, removing the need to use the Fujitsu TeamCom retail I/O card

Available Peripherals



TEAMPOS 2000 LITE SPECIFICATIONS

Control Unit	Processor:	Celeron 566MHz
	Memory:	64MB standard (Expandable to 256MB, 2 slot)
	File devices:	HDD: 20GB
	FDD:	720KB/1.44MB
	CD-ROM drive:	Maximum 24x speed (Option)
	I/O Interface:	2 x RS232 with +5V 2 x RS232 with +24V 1 x Keyboard 1 x Mouse 2 x USB
	Expansion slots:	PCI x 2
	On board LAN:	100 Base - TX/10 Base-T
	Size:	340mm (W) x 450 mm(D) x 115mm (H)
Operator Display		10" or 12" Flat Panel Displays, (all VGA)
Customer Display		20 x 2 Alphanumeric VFD -12" FPD rear-mounted type -Remote pole mounted type
Keyboard		104-key programmable with 4-position cylinder lock 133PQ Keyboard 92M Keyboard
MSR		ISO Track 1/2/3 integrated into keyboard (Optional)
Printer	1-station thermal:	2-colour or monochrome printing 180mm per second <80mm width paper RS232 Interface ESC/POS protocol
	2-station	Receipt:
	Thermal/dot matrix:	-56 columns thermal, 80mm paper, print speed 150mm per second Slip/Cheque: -60 columns impact -70-148mm paper RS232 Interface ESC/POS protocol
Cash Drawer	Compact size:	3 compartments for bills, 6 compartments for coins 330mm(W) x 420mm(D) x 107mm(H)
	Standard size:	5 compartments for bills, 6 compartments for coins, Media slot 450mm(W) x 501mm(D) x 123mm(H)

FUJITSU SERVICES

Observatory House, Windsor Road, Slough, Berks SL1 2EY United Kingdom
Tel: +44 (0) 870 242 7998 Fax: +44 (0) 870 242 4445
Email: askfujitsu@services.fujitsu.com Web: uk.fujitsu.com